



DURATURN
EXTRAORDINARY TIRES AT ANY PRICE



CONSUMER TIRES | 2018



TABLE OF CONTENTS

3	ABOUT DURATURN
4	PASSENGER & CUV TIRES
8	PERFORMANCE TIRES
12	LIGHT TRUCK & SUV TIRES
18	WINTER TIRES
21	SPECIALTY TIRES
22	LIMITED WARRANTY

DURATURN

At Duraturn, we're obsessed with being more than just dependable, more than just a maker of quality performance tires, more than just a great value. That passion drives us to build extraordinary products that would be extraordinary at any price.

With one of the most sophisticated manufacturing facilities on Earth, we harness the power of innovation to engineer tires that deliver exhilarating performance, proven safety, long life AND lasting value.

PASSENGER AND CUV



- Four see-through grooves enhance water evacuation
- Siped solid center rib improves steering response and extra biting edges for grip
- Variable shoulder blocks provide a quieter, more comfortable ride
- Optimized tread blocks move water towards evacuation channels and provide additional siping for better braking performance

30 DAY SATISFACTION GUARANTEE

MOZZO TOURING

70K MILEAGE WARRANTY

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG RATING	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
1017	165/70R13 79T	SL	BW	500 A A	10	6.7	22.1	963	51	14	1P+2S
1000	175/70R13 82T	SL	BW	560 A A	11	7.0	22.7	1047	51	15	1P+2S
1018	165/65R13 77T	SL	BW	500 A A	10	6.7	21.4	853	51		1P+2S
1019	175/70R14 84T	SL	BW	560 A A	11	7.0	23.7	1102	51	17	1P+2S
1020	185/70R14 88T	SL	BW	560 A A	11	7.4	24.3	1235	51	18	1P+2S+1N
1001	195/70R14 91T	SL	BW	560 A A	11	7.9	24.8	1356	51	20	1P+2S
1021	175/65R14 82H	SL	BW	560 A A	11	7.0	23.0	1047	51	16	1P+2S+1N
1002	185/65R14 86H	SL	BW	560 A A	11	7.4	23.5	1168	51	17	1P+2S+1N
1022	185/60R14 82H	SL	BW	560 A A	11	7.4	22.8	1047	51	16	1P+2S
1023	195/60R14 86H	SL	BW	560 A A	11	7.9	23.2	1168	51	18	1P+2S+1N
1003	205/70R15 96T	SL	BW	560 A A	11	8.2	26.3	1565	51	23	2P+2S
1004	215/70R15 98T	SL	BW	560 A A	11	8.7	26.9	1653	51	24	2P+2S
1005	195/65R15 91H	SL	BW	560 A A	11	7.9	25.0	1356	51	21	1P+2S+1N
1006	205/65R15 99T	XL	BW	560 A A	11	8.2	25.5	1709	50	22	2P+2S+1N
1024	185/60R15 84H	SL	BW	560 A A	11	7.4	23.7	1102	51	17	1P+2S+1N
1007	195/60R15 88H	SL	BW	560 A A	11	7.9	24.2	1235	51	20	1P+2S+1N
1025	205/65R16 95V	SL	BW	560 A A	11	8.2	26.5	1521	51	24	2P+2S+1N
1008	215/65R16 98H	SL	BW	560 A A	11	8.7	27.0	1653	51	25	2P+2S+1N
1009	205/60R16 92V	SL	BW	560 A A	11	8.2	25.7	1389	51	23	1P+2S+1N
1010	215/60R16 95V	SL	BW	560 A A	11	8.7	26.1	1521	51	24	2P+2S+1N
1011	225/60R16 98H	SL	BW	560 A A	11	9.0	26.6	1653	51	26	2P+2S+1N
1012	205/55R16 91V	SL	BW	560 A A	11	8.4	24.9	1356	51	22	1P+2S+1N
1013	225/65R17 102H	SL	BW	560 A A	11	9.0	28.5	1874	51	28	2P+2S+1N
1026	235/65R17 104H	SL	BW	560 A A				under development			
1028	235/60R17 102T	SL	BW	560 A A				under development			
1029	215/55R17 94V	SL	BW	560 A A				under development			
1014	215/50R17 95V	XL	BW	560 A A	11	8.9	25.5	1521	50	23	1P+2S+1N
1015	225/50R17 94V	SL	BW	560 A A	11	9.2	25.9	1477	51	26	2P+2S+1N
1016	235/55R18 100V	SL	BW	560 A A	11	9.7	28.2	1764	51	30	2P+2S+1N

MOZZO S360

50K MILEAGE WARRANTY

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG RATING	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
1401	225/65R17 102H	SL	BW	500 A A	10	9.0	28.5	1874	51	25	2P+2S+1N
1402	215/55R17 94V	SL	BW	500 A A	10	8.9	26.3	1477	51	23	1P+2S+1N
1403	225/60R18 100H	SL	BW	500 A A	10	9.0	28.6	1764	51	27	2P+2S+1N
1404	225/55R18 98V	SL	BW	500 A A	10	9.2	27.8	1653	51	26	2P+2S+1N



- All Season tread design
- 3 circumferential grooves for rapid water evacuation and extra grip on wet pavement
- Assymetric tread design for improved handling and cornering
- New silica tread compound improves grip and reduces rolling resistance

MOZZO 4S

45K MILEAGE WARRANTY



- All season tread design
- Four circumferential grooves for rapid water evacuation and extra grip on wet pavement
- Solid center rib for improved steering response
- Assymetric tread design for improved handling and cornering
- New silica tread compound improves grip and reduces rolling resistance

MOZZO 4S+

50K MILEAGE WARRANTY

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG RATING	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
1192	145/70R12 69T	SL	BW	400 A A	9	5.91	20.04	723	51		1P+2S
1150	165/70R13 79T	SL	BW	400 A A	9	6.69	22.13	963	51	13	1P+2S
1151	175/70R13 82T	SL	BW	400 A A	9	6.97	22.68	1047	51	14	1P+2S
1193	185/70R13 86T	SL	BW	400 A A	9	7.44	23.23	1168	51	15	1P+2S
1194	165/70R14 81T	SL	BW	400 A A	9	6.69	23.15	1019	51	13	1P+2S
1153	175/70R14 84T	SL	BW	400 A A	9	6.97	23.70	1102	51	15	1P+2S
1195	185/70R14 88T	SL	BW	400 A A	9	7.44	24.25	1235	51	16	1P+2S+1N
1152	175/65R14 82H	SL	BW	400 A A	9	6.97	22.99	1047	51	14	1P+2S+1N
1211	175/65R14 82T	SL	BW	400 A A	9	6.97	22.99	1047	51	14	1P+2S
1196	185/65R14 86H	SL	BW	400 A A	9	7.44	23.46	1168	51	15	1P+2S+1N
1197	185/65R14 90S	XL	BW	400 A A	9	7.44	23.46	1323	50	15	1P+2S+1N
1198	165/60R14 75H	SL	BW	400 A A	9	6.69	21.81	853	51	13	1P+2S+1N
1154	185/60R14 82H	SL	BW	400 A A	9	7.44	22.76	1047	51	14	1P+2S+1N
1199	155/55R14 69H	SL	BW	400 A A	9	6.38	20.71	723	51	11	1P+2S+1N
1200	165/55R14 72H	SL	BW	400 A A	9	6.69	21.18	783	51	13	1P+2S+1N
1155	175/65R15 84H	SL	BW	400 A A	9	6.97	23.98	1102	51	16	1P+2S+1N
1201	185/65R15 88H	SL	BW	400 A A	9	7.44	24.45	1235	51	17	1P+2S+1N
1202	185/60R15 84H	SL	BW	400 A A	9	7.44	23.74	1102	51	16	1P+2S+1N
1191	165/55R15 75V	SL	BW	400 A A	9	6.69	22.17	853	51	13	1P+2S+1N
1187	165/55R15 75H	SL	BW	400 A A	9	6.69	22.17	853	51	13	1P+2S+1N
1173	185/55R15 82V	SL	BW	400 A A	9	7.64	23.03	1047	51	16	1P+2S+1N
1186	165/50R15 72V	SL	BW	400 A A	9	6.69	21.54	783	51	13	1P+2S+1N
1190	165/50R15 72H	SL	BW	400 A A	9	6.69	21.54	783	51	13	1P+2S+1N
1189	165/45R16 74V	XL	BW	400 A A	9	6.50	21.81	739	51	13	1P+2S+1N
1184	165/40R16 70V	XL	BW	400 A A	9	6.69	21.18	739	50	12	1P+2S+1N
1188	165/40R16 73V	XL	BW	400 A A	9	6.69	21.18	805	50	12	1P+2S+1N

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG RATING	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
1157	195/70R14 91T	SL	BW	400 A A	10	7.91	24.80	1356	51 psi	19	1P+2S
1203	205/60R14 88V	SL	BW	400 A A	10	8.23	23.70	1235	51 psi	18	1P+2S+1N
1175	195/65R15 91V	SL	BW	400 A A	10	7.91	25.00	1356	51 psi	19	1P+2S+1N
1158	195/65R15 91H	SL	BW	400 A A	10	7.91	25.00	1356	51 psi	19	1P+2S+1N
1205	205/65R15 94V	SL	BW	400 A A	10	8.23	25.47	1477	51 psi	20	1P+2S+1N
1204	205/65R15 94H	SL	BW	400 A A	10	8.23	25.47	1477	51 psi	20	1P+2S+1N
1178	195/60R15 88V	SL	BW	400 A A	10	7.91	24.21	1235	51 psi	18	1P+2S+1N
1161	195/60R15 88H	SL	BW	400 A A	10	7.91	24.21	1235	51 psi	17	1P+2S+1N
1210	205/60R15 91H	SL	BW	400 A A	10	8.23	24.69	1356	51 psi	20	1P+2S+1N
1206	205/60R15 91V	SL	BW	400 A A	10	8.23	24.69	1356	51 psi	20	1P+2S+1N
1177	195/55R15 85V	SL	BW	400 A A	10	7.91	23.43	1135	51 psi	16	1P+2S+1N
1176	195/50R15 82V	SL	BW	400 A A	10	7.91	22.72	1047	51 psi	16	1P+2S+1N
1209	205/60R16 92H	SL	BW	400 A A	10	8.23	25.67	1389	51 psi	20	1P+2S+1N
1165	215/60R16 95H	SL	BW	400 A A	10	8.70	26.14	1521	51 psi	23	2P+2S+1N
1182	215/60R16 95V	SL	BW	400 A A	10	8.70	26.14	1521	51 psi	23	2P+2S+1N
1166	225/60R16 98H	SL	BW	400 A A	10	8.98	26.61	1653	51 psi	23	2P+2S+1N
1179	195/55R16 91V	XL	BW	400 A A	10	7.91	24.41	1201	51 psi	18	1P+2S+1N
1181	205/55R16 91V	SL	BW	400 A A	10	8.43	24.88	1356		20	1P+2S+1N
1164	205/55R16 91H	SL	BW	400 A A	10	8.43	24.88	1356	51 psi	20	1P+2S+1N
1180	205/50R16 87V	SL	BW	400 A A	10	8.43	24.09	1201	51 psi	19	1P+2S+1N
1207	205/45R16 83V	SL	BW	400 A A	10	8.11	23.23	1074	51 psi	17	1P+2S+1N
1208	205/40R17 84W	XL	BW	400 A A	10	8.35	23.46	1102	51 psi	17	1P+2S+1N

PERFORMANCE



- M+S rated tires designed for performance in dry, wet, and light snow conditions
- Circumferential grooves quickly move water out of the tire footprint
- Spiral wrap technology improves uniformity and protects against heat buildup
- Variable pitch sequence reduces road noise by varying the size of the shoulder and tread blocks
- Solid center rib improves steering response and handling



MOZZO STX

50K MILEAGE WARRANTY

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG RATING	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
1268	225/65R17 106V	XL	BW	460 A A	11	8.98	28.50	2094	50	29	2P+2S+1N
1269	225/60R17 103V	XL	BW	460 A A	11	8.98	27.64	1929	50	28	2P+2S+1N
1250	275/60R20 115V	SL	BW	460 A A	11	10.98	32.99	2679	51	40	2P+2S+1N
1251	275/55R20 117V	XL	BW	460 A A	11	11.18	31.89	2833	50	38	2P+2S+1N
1252	265/50R20 111V	XL	BW	460 A A	11	10.91	30.47	2403	50	36	2P+2S+1N
1253	285/50R20 116V	XL	BW	460 A A	11	11.69	31.26	2756	50	39	2P+2S+1N
1254	275/45R20 110V	XL	BW	460 A A	11	10.75	29.76	2337	50	34	2P+2S+1N
1255	245/40R20 99W	XL	BW	460 A A	11	9.76	27.72	1709	50	28	2P+2S+1N
1256	275/40R20 106V	XL	BW	460 A A	11	10.94	28.66	2094	50	33	2P+2S+1N
1257	285/45R22 114V	XL	BW	460 A A	11	11.22	32.09	2601	50	38	2P+2S+1N
1258	305/45R22 118V	XL	BW	460 A A	11	11.93	32.80	2910	50	41	2P+2S+1N
1259	265/40R22 106V	XL	BW	460 A A	11	10.67	30.35	2094	50	34	2P+2S+1N
1260	305/40R22 114V	XL	BW	460 A A	11	12.32	31.61	2601	50	40	2P+2S+1N
1261	265/35R22 102V	XL	BW	460 A A	11	10.67	29.33	1874	50	33	2P+2S+1N
1262	245/30R22 92W	XL	BW	460 A A	11	9.76	27.83	1389	50	28	1P+2S+1N
1264	295/35R24 110V	XL	BW	460 A A	11	11.85	32.13	2337	50	39	2P+2S+1N
1263	305/35R24 112V	XL	BW	460 A A	11	12.32	32.44	2469	50	41	2P+2S+1N
1265	255/30R24 97W	XL	BW	460 A A	11	10.24	30.08	1609	50	32	2P+2S+1N
1266	295/30R26 107W	XL	BW	460 A A	11	11.85	32.99	2149	50	39	2P+2S+1N
1267	305/30R26 109V	XL	BW	460 A A	11	12.32	33.23	2271	50	40	2P+2S+1N



- Four see-through grooves enhance water evacuation
- Siped solid center rib improves steering response and extra biting edges for grip
- Variable shoulder blocks provide a quieter, more comfortable ride
- Optimized tread blocks move water towards the evacuation channels and provide additional siping for better braking performance

MOZZO SPORT

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG RATING	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
1300	205/55R16 91/94W	SL	BW	500 A A	10	8.43	24.88	1356	51	22	1P+2S+1N
1317	215/55R16 97W	XL	BW	500 A A	10	8.90	25.28	1609	50	23	1P+2S+1N
1316	225/55R16 99W	XL	BW	500 A A	10	9.17	25.75	1709	50	24	2P+2S+1N
1335	225/55R17 101W	XL	BW	500 A A	10	9.17	26.77	1819	50	26	2P+2S+1N
1301	235/55R17 103W	XL	BW	500 A A	10	9.65	27.17	1929	50	28	2P+2S+1N
1302	205/50R17 93W	XL	BW	500 A A	10	8.43	25.12	1433	50	23	1P+2S+1N
1340	215/50R17 95W	XL	BW	500 A A	10	8.90	25.50	1521	50	23	1P+2S+1N
1303	225/50R17 98W	XL	BW	500 A A	10	9.17	25.91	1653	50	26	2P+2S+1N
1341	235/50R17 100W	XL	BW	500 A A	10	9.70	26.30	1764	50	27	2P+2S+1N
1318	215/45R17 91W	XL	BW	500 A A	10	8.39	24.65	1356	50	21	1P+2S+1N
1304	225/45R17 94W	XL	BW	500 A A	10	8.86	24.96	1477	50	23	1P+2S+1N
1319	235/45R17 97W	XL	BW	500 A A	10	9.29	25.35	1609	50	24	2P+2S+1N
1305	245/45R17 99W	XL	BW	500 A A	10	9.57	25.67	1709	50	25	2P+2S+1N
1320	205/40R17 84W	XL	BW	500 A A	10	8.35	23.46	1102	50	19	1P+2S+1N
1306	255/40R17 98W	XL	BW	500 A A	10	10.24	25.04	1653	50	26	2P+2S+1N
1336	255/55R18 109W	XL	BW	500 A A	10	10.43	29.02	2271	50	31	2P+2S+1N
1307	235/50R18 101W	XL	BW	500 A A	10	9.65	27.28	1819	50	28	2P+2S+1N
1337	245/50R18 104W	XL	BW	500 A A	10	9.96	27.68	1984	50	29	2P+2S+1N
1308	225/45R18 95W	XL	BW	500 A A	10	8.86	25.94	1521	50	23	1P+2S+1N
1309	245/45R18 100W	XL	BW	500 A A	10	9.57	26.65	1764	50	27	2P+2S+1N
1321	255/45R18 103W	XL	BW	500 A A	10	10.04	27.05	1929	50	27	2P+2S+1N
1322	215/40R18 89W	XL	BW	500 A A	10	8.58	24.76	1279	50	21	1P+2S+1N
1310	225/40R18 92W	XL	BW	500 A A	10	9.06	25.08	1389	50	22	1P+2S+1N
1311	235/40R18 95W	XL	BW	500 A A	10	9.49	25.39	1521	50	24	1P+2S+1N
1312	245/40R18 97W	XL	BW	500 A A	10	9.76	25.71	1609	50	26	2P+2S+1N
1313	255/35R18 94Y	XL	BW	500 A A	10	10.24	25.00	1477	50	25	1P+2S+1N
1323	265/35R18 97Y	XL	BW	500 A A	10	10.67	25.31	1609	50	25	2P+2S+1N
1338	255/50R19 107W	XL	BW	500 A A	10	10.43	29.09	2150	50	32	2P+2S+1N
1342	245/45R19 102W	XL	BW	500 A A	10	9.57	26.65	1764	50	27	2P+2S+2N
1324	255/45R19 104W	XL	BW	500 A A	10	10.04	28.07	1984	50	29	2P+2S+1N
1326	245/40R19 98W	XL	BW	500 A A	10	9.76	26.73	1653	50	27	2P+2S+2N
1325	255/40R19 100W	XL	BW	500 A A	10	10.24	27.05	1764	50	28	2P+2S+1N
1327	215/35R19 85Y	XL	BW	500 A A	10	8.58	24.92	1135	50	20	1P+2S+1N
1328	225/35R19 88Y	XL	BW	500 A A	10	9.06	25.24	1235	50	21	1P+2S+1N
1329	235/35R19 91Y	XL	BW	500 A A	10	9.49	26.54	1356	50	24	1P+2S+1N
1330	245/35R19 93Y	XL	BW	500 A A	10	9.76	25.79	1433	50	25	1P+2S+1N
1331	265/30R19 93Y	XL	BW	500 A A	10	10.67	25.31	1433	50	26	1P+2S+1N
1332	275/30R19 96Y	XL	BW	500 A A	10	10.94	25.55	1565	50	27	2P+2S+1N
1314	245/45R20 99W	SL	BW	500 A A	10	9.57	28.66	1709	51	29	2P+2S+1N
1339	275/40R20 106W	XL	BW	500 A A	10	10.94	28.66	2094	50	31	2P+2S+1N
1333	225/35R20 90Y	XL	BW	500 A A	10	9.06	26.22	1323	50	22	1P+2S+1N
1334	245/35R20 95Y	XL	BW	500 A A	10	9.76	26.77	1521	50	26	1P+2S+1N
1315	255/35R20 97Y	XL	BW	500 A A	10	10.24	27.01	1609	50	27	2P+2S+1N
1343	245/30R20 90W	XL	BW	500 A A	10	9.80	25.80	1323	50	25	2P+2S+1N
1344	275/30R20 97W	XL	BW	500 A A	10	10.9	27.70	1609	50	30	2P+2S+1N



LIGHT TRUCK AND SUV

- 5 rib tread design for maximizing traction on the road
- Multiple zig-zag sipes provide increased biting edges
- Circumferential grooves enhance water evacuation
- Special shoulder block design improves handling and cornering ability
- Jointless nylon spiral wrap cap ply for improved uniformity and resistance to heat buildup

30 DAY SATISFACTION GUARANTEE

TRAVIA H/T

60K MILEAGE WARRANTY



TRAVIA A/T

- 5 rib tread design for longer road wear
- Specially designed tread blocks provide extra traction in off-road conditions
- 2-step tread blocks for additional stability in the contact patch
- Cleaning bars within the tread design help to keep tread area clean from mud and debris
- Variable pitch tread blocks to reduce road noise
- Jointless Nylon spiral wrap cap ply for improved uniformity and resistance to heat buildup

50K MILEAGE WARRANTY

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG RATING	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
2100	235/75R15 109T	XL	OWL	640 A A	12	9.25	28.86	2271	50	30	2P+2S+1N
2101	265/75R16 116T	SL	OWL	640 A A	12	10.51	31.65	2756	51	38	2P+2S+1N
2102	215/70R16 100H	SL	OWL	640 A A	12	8.70	27.87	1764	51	27	2P+2S+1N
2103	225/70R16 103T	SL	OWL	640 A A	12	8.98	28.43	1929	51	29	2P+2S+1N
2104	235/70R16 106T	SL	OWL	640 A A	12	9.45	28.98	2094	51	30	2P+2S+1N
2105	245/70R16 107T	SL	OWL	640 A A	12	9.76	29.53	2403	51	32	2P+2S+1N
2115	255/70R16 111T	SL	OWL	640 A A	under development						
2106	265/70R16 112T	SL	OWL	640 A A	12	10.71	30.63	2469	51	35	2P+2S+1N
2114	245/75R16 111T	SL	OWL	640 A A	under development						
2107	265/70R17 115T	SL	OWL	640 A A	12	10.71	31.65	2679	51	37	2P+2S+1N
2108	235/65R17 104T	SL	BSW	640 A A	12	9.45	29.06	1984	51	31	2P+2S+1N
2109	245/65R17 107T	SL	BSW	640 A A	12	9.76	29.53	2149	51	33	2P+2S+1N
2110	265/65R17 112H	SL	OWL	640 A A	12	10.71	30.55	2469	51	36	2P+2S+1N
2111	215/60R17 96H	SL	OWL	640 A A	12	8.70	27.17	1565	51	27	2P+2S+1N
2119	265/65R18 114T	SL	OWL	640 A A	under development						
2112	235/60R18 103H	SL	OWL	640 A A	12	9.45	29.09	1929	51	30	2P+2S+1N
2122	265/60R18 110T	SL	OWL	640 A A	under development						
2113	215/55R18 95H	SL	OWL	640 A A	12	8.90	27.28	1521	51	26	2P+2S+1N
2124	275/55R20 117H	XL	BSW	640 A A	under development						
2185	LT215/75R15 106/103R	D	BSW		14	8.50	27.68	2095/1930	65	35	2P+2S+1N
2186	LT235/75R15 116/113S	E	BSW		14	9.25	28.86	2755/2535	80	38	2P+2S+1N
2175	LT31X10.50R15 109R	C	BSW		14	10.55	30.51	2270	50	39	2P+2S+1N
2176	LT235/85R16 120/116R	E	BSW		14	9.25	31.73	3042/2778	80	40	2P+2S+1N
2177	LT225/75R16 115/112R	E	BSW		14	8.78	29.29	2680/2470	80	36	2P+2S+1N
2178	LT245/75R16 120/116R	E	BSW		14	9.76	30.47	3042/2778	80	40	2P+2S+1N
2179	LT265/75R16 123/120R	E	BSW		14	10.51	31.65	3415/3085	80	44	2P+2S+1N
2181	LT235/80R17 120/117R	E	BSW		14	9.25	31.81	3085/2835	80	41	2P+2S+1N
2182	LT245/75R17 121/118R	E	BSW		14	9.76	31.5	3195/2910	80	41	2P+2S+1N
2183	LT265/70R17 121/118R	E	BSW		14	10.71	31.65	3195/2910	80	45	2P+2S+1N
2184	LT285/70R17 121/118S	D	BSW		14	11.50	32.76	3195/2910	65	50	2P+2S+1N

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG RATING	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION	STUD
2200	215/75R15 100T	SL	OWL	500 A A	13	8.50	27.68	1763	51	28	2P+2S+1N	12
2201	235/75R15 109T	XL	OWL	500 A A	13	9.25	28.86	2271	50	34	2P+2S+1N	12
2202	265/75R16 116T	SL	OWL	500 A A	13	10.51	31.65	2756	51	39	2P+2S+1N	12
2203	215/70R16 100H	SL	OWL	500 A A	13	8.70	27.87	1764	51	29	2P+2S+1N	12
2204	225/70R16 103T	SL	OWL	500 A A	13	8.98	28.43	1929	51	31	2P+2S+1N	12
2205	235/70R16 106T	SL	OWL	500 A A	13	9.45	28.98	2094	51	28	2P+2S+1N	12
2206	245/70R16 107T	SL	OWL	500 A A	13	9.76	29.53	2149	51	34	2P+2S+1N	12
2207	265/70R16 112T	SL	OWL	500 A A	13	10.70	30.63	2469	51	38	2P+2S+1N	12
2208	265/70R17 115T	SL	OWL	500 A A	13	10.71	31.65	2679	51	40	2P+2S+1N	12
2209	235/65R17 104T	SL	BSW	500 A A	13	9.45	29.06	1984	51	32	2P+2S+1N	12
2210	245/65R17 107T	SL	BSW	500 A A	13	9.76	29.53	2149	51	34	2P+2S+1N	12
2211	265/65R17 112H	SL	OWL	500 A A	13	10.71	30.55	2469	51	37	2P+2S+1N	12
2261	LT235/75R15 116/113S	E	BSW		16	9.25	28.86	2755/2535	80	38	2P+2S+1N	15
2251	LT31X10.50R15 109R	C	OWL		16	10.55	30.51	2270	50	41	2P+2S+1N	15
2252	LT235/85R16 120/116R	E	BSW		16	9.25	31.73	3042/2778	80	44	2P+2S+1N	15
2253	LT225/75R16 115/112R	E	BSW		16	8.78	29.29	2680/2470	80	38	2P+2S+1N	15
2254	LT245/75R16 120/116R	E	OWL		16	9.76	30.47	3042/2778	80	43	2P+2S+1N	15
2255	LT265/75R16 123/120R	E	OWL		16	10.51	31.65	3415/3085	80	47	2P+2S+1N	15
2256	LT285/75R16 126/123R	E	OWL		16	11.26	32.83	3750/3415	80	52	2P+2S+1N	15
2257	LT235/80R17 120/117R	E	OWL		16	9.25	31.81	3085/2835	80	44	2P+2S+1N	15
2258	LT245/75R17 121/118R	E	OWL		16	9.76	31.50	3195/2910	80	45	2P+2S+1N	15
2265	LT245/70R17 119/116S	E	OWL		under development							
2259	LT265/70R17 121/118R	E	OWL		16	10.71	31.65	3195/2910	80	48	2P+2S+1N	15
2260	LT285/70R17 121/118S	D	BSW		16	11.50	32.76	3195/2910	65	53	2P+2S+1N	15
2266	LT275/70R18 125/122S	E	OWL		under development							
2268	LT275/65R20 126/123S	E	OWL		under development							



TRAVIA M/T



- Large tread blocks and shoulder lugs for maximum traction in off-road terrain
- Cleaning bars between tread blocks loosen and evacuate mud and dirt
- Sidebiters for additional off-road traction and additional resistance to cuts and abrasions
- Alternating concave/convex shoulder blocks offers additional off-road performance
- Jointless nylon spiral wrap cap ply for improved uniformity and resistance to heat buildup

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG RATING	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION	STUD
2303	LT245/75R16 120/116Q	E	BSW	19	9.80	30.50	3042/2778	80	46	46	2P+2S+1N	15
2304	LT265/75R16 123/120R	E	BSW	19	10.51	31.65	3415/3085	80	49	49	2P+2S+1N	15
2305	LT285/75R16 126/123Q	E	OWL	19	11.30	32.80	3750/3415	80	55	55	2P+2S+1N	15
2307	LT265/70R17 121/118Q	E	OWL	19	10.70	31.70	3195/2910	80	50	50	2P+2S+1N	15
2308	LT285/70R17 121/118Q	E	OWL	19	11.50	32.80	3195/2910	80	54	54	2P+2S+1N	15
2313	31X10.50R15LT 109Q	C	OWL	19	10.60	30.50	2270	50	43	43	2P+2S+1N	15
2318	33X12.50R18LT 118Q	E	BSW	19	12.50	32.50	2910	80	59	59	2P+2S+1N	15
2320	33X12.50R20LT 114Q	E	BSW	19	12.50	32.50	2600	80	59	59	2P+2S+1N	15
2321	35X12.50R20LT 121Q	E	BSW	19	12.50	34.50	3195	80	63	63	2P+2S+1N	15



TRAVIA VAN

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG RATING	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
2618	155R12C 88/86Q		BSW		13	6.18	21.65	1235/1168	6	16	2P+2S+1N
2619	155R13C 85/83Q		BSW		13	6.18	22.76	1135/1074	51	16	2P+2S+1N
2620	165R13C 91/89Q		BSW		13	6.57	23.46	1356/1279	54	17	2P+2S+1N
2621	165/70R13C 88/86R		BSW		13	6.69	22.13	1235/1168	54	17	2P+2S+1N
2600	185R14C 102/100Q		OWL		13	7.40	25.59	1874/1764	65	23	2P+2S+1N
2601	195R14C 106/104Q		OWL		13	7.80	26.22	2094/1984	65	25	2P+2S+1N
2602	205R14C 109/107Q		OWL		13	8.19	27.01	2271/2149	65	26	2P+2S+1N
2622	165/70R14C 89/87R		BSW		13	6.69	23.15	1279/1201	54	17	2P+2S+1N
2623	175/70R14C 95/93R		BSW		13	6.97	23.70	1521/1433	54	17	2P+2S+1N
2603	195R15C 106/104R		OWL		13	7.72	27.28	2094/1984	65	25	2P+2S+1N
2607	195/70R15C 104/102R		BSW		13	7.91	25.79	1984/1874	65	24	2P+2S+1N
2605	205/70R15C 106/104R		BSW		13	8.23	26.34	2094/1984	65	26	2P+2S+1N
2615	215/70R15C 109/107R		BSW		13	8.70	26.89	2271/2149	65	27	2P+2S+1N
2606	225/70R15C 112/110R		BSW		13	8.98	27.44	2469/2337	65	29	2P+2S+1N
2604	205R16C 110/108R		OWL		13	8.19	28.98	2337/2205	65	29	2P+2S+1N
2613	185/75R16C 104/102R		BSW		13	7.24	26.93	1984/1874	69	25	2P+2S+1N
2611	195/75R16C 107/105R		BSW		13	7.72	27.48	2149/2039	69	26	2P+2S+1N
2609	205/75R16C 110/108R		BSW		13	7.99	28.11	2337/2205	69	27	2P+2S+1N
2608	215/75R16C 113/111R		BSW		13	8.50	28.66	2535/2403	69	29	2P+2S+1N
2612	205/65R16C 107/105T		BSW		13	8.23	26.46	2149/2039	69	26	2P+2S+1N
2610	215/65R16C 109/107R		BSW		13	8.70	27.01	2271/2149	69	28	2P+2S+1N
2616	225/65R16C 112/110R		BSW		13	8.98	27.48	2469/2337	69	29	2P+2S+1N
2614	215/60R16C 103/101T		BSW		13	8.70	26.14	1929/1819	54	27	2P+2S+1N
2617	235/65R16C 115/113R		BSW		13	9.45	28.03	2679/2535	69	31	2P+2S+1N
2626	235/65R16C 121/119R		BSW					under development			

WINTER

- Studdable design for increased traction and better performance in ice and snow conditions with studs applied
- V shaped design with a multi-siped center rip for improved handling and grip performance
- Softer winter tire compound to maintain performance in winter temperatures
- Zig-zag grooves designed to enhance traction for snowy conditions



MOZZO WINTER ICE

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	STUD	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
1800	165/70R13 79T	SL	BW	12	13	6.69	22.13	963	51	14	1P+2S
1809	175/70R13 82T	SL	BW	12	13	6.97	22.68	1047	51	16	1P+2S
1801	205/70R14 98T	XL	BW	12	13	8.23	25.35	1653	50	22	2P+2S+1N
1803	175/65R14 82T	SL	BW	12	13	6.97	22.99	1047	51	17	1P+2S
1804	185/65R14 86T	SL	BW	12	13	7.44	23.46	1168	51	18	1P+2S
1810	185/60R14 82T	SL	BW	12	13	7.44	22.76	1047	51	17	1P+2S
1802	195/60R14 86T	SL	BW	12	13	7.91	23.23	1168	51	18	1P+2S
1808	235/75R15 105T	SL	BW	12	13	9.25	28.86	2039	51	30	2P+2S+1N
1811	205/70R15C 106/104R		BW	12	13	8.23	26.34	4189	51	26	2P+2S+1N
1807	185/65R15 88T	SL	BW	12	13	7.44	24.57	1235	51	18	1P+2S
1805	195/65R15 91T	SL	BW	12	13	7.91	25.00	1356	51	20	1P+2S
1812	185/75R16C 104/102R		BW	12	13	7.24	26.93	3968	51	25	2P+2S+1N
1806	235/70R16 106T	SL	BW	12	13	9.45	28.98	2094	51	29	2P+2S+1N
1815	225/60R16 98T	SL	BW	12	13	8.98	26.61	1653	51	26	2P+2S+1N
1814	205/55R16 91T	SL	BW	12	13	8.43	24.88	1356	51	21	1P+2S
1813	235/65R17 108T	XL	BW	12	13	9.45	29.06	2205	50	30	2P+2S+1N

TRAVIA WINTER

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	STUD	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
1901	225/65R17 102H	SL	BW		13	8.98	28.50	1874	51	29	2P+2S+1N

WINTER

- Studless design with multiple zig-zag sipes for more biting edges in snowy conditions
- Softer winter tire compound to maintain performance in winter temperatures
- Directional pattern offers increased traction



MOZZO WINTER

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	STUD	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
1701	175/70R13 82T	SL	BSW		11	6.97	22.678	1047	51	14	1P+2S
1700	165/70R14 81T	SL	BSW		11	6.69	23.15	1019	51	14	1P+2S
1703	175/70R14 84T	SL	BSW		11	6.97	23.70	1102	51	16	1P+2S
1702	175/65R14 82T	SL	BSW		11	6.97	22.99	1047	51	15	1P+2S
1705	185/65R14 86H	SL	BSW		11	7.44	23.46	1168	51	16	1P+2S+1N
1704	185/60R14 82H	SL	BSW		11	7.44	22.76	1047	51	14	1P+2S
1708	185/65R15 88H	SL	BSW		11	7.44	24.44	1235	51	17	1P+2S+1N
1713	195/65R15 91H	SL	BSW		11	7.91	25.00	1356	51	19	1P+2S+1N
1714	205/65R15 94H	SL	BSW		11	8.23	25.47	1477	51	21	1P+2S+1N
1706	185/60R15 84H	SL	BSW		11	7.44	23.74	1102	51	17	1P+2S+1N
1710	195/60R15 88H	SL	BSW		11	7.91	24.21	1235	51	18	1P+2S+1N
1709	195/55R15 85H	SL	BSW		11	7.91	23.43	1135	51	18	1P+2S+1N
1720	215/65R16 98H	SL	BSW		11	8.70	27.01	1653	51	24	2P+2S+1N
1715	205/60R16 92H	SL	BSW		11	8.23	25.67	1389	51	20	1P+2S+1N
1718	215/60R16 95V/H	SL	BSW		11	8.70	26.14	1521	51	23	2P+2S+1N
1711	195/55R16 91H	XL	BSW		11	7.91	24.41	1201	51	19	1P+2S+1N
1717	205/55R16 91V	SL	BSW		11	8.43	24.88	1356	51	21	1P+2S+1N
1724	215/55R16 97V	XL	BSW		11	8.90	25.28	1433	51	23	2P+2S+1N
1728	225/55R16 99H	XL	BSW		11	9.17	25.75	1521	51	23	2P+2S+1N
1731	215/55R17 98V	XL	BSW		11	under development					
1722	225/45R17 94V	XL	BSW		11	8.86	24.96	1356	51	22	2P+2S+1N
1725	225/40R18 92V	XL	BSW		11	9.06	25.08	1235	51	22	2P+2S+1N

SPECIALTY

- Circumferential grooves evacuate water in order to resist hydroplaning
- Spiral wrap technology improves uniformity and prohibits heat buildup
- Dual angled sipes provide additional biting edges for extra grip on the road
- Continuous center ribs keep the trailer on track behind the tow vehicle



ST RADIAL

PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG RATING	TREAD DEPTH (32NDS)	SECTION WIDTH	OVERALL DIAMETER	MAX LOAD SINGLE/DUAL	MAX PRESSURE	WEIGHT (LB)	TREAD CONSTRUCTION
5900	ST175/80R13 91/87L	C	BW	---	10	6.97	24.02	1360/1200	60	16	1P+2S
5901	ST185/80R13 94/89L	C	BW	---	10	7.24	24.65	1480/1280	60	17	1P+2S
5902	ST205/75R14 100/96L	C	BW	---	10	7.99	26.14	1760/1570	60	20	2P+2S
5905	ST215/75R14 102/98L	C	BW	---	10	8.50	26.69	1870/1650	60	22	2P+2S
5903	ST205/75R15 101/97L	C	BW	---	10	7.99	27.13	1820/1610	60	22	2P+2S+1N
5904	ST205/75R15 107/102L	D	BW	---	10	7.99	27.13	2150/1870	75	23	2P+2S+1N
5906	ST225/75R15 107/102L	C	BW	---	10	8.78	28.31	2150/1870	60	25	2P+2S+1N
5907	ST225/75R15 113/108L	D	BW	---	10	8.78	28.31	2540/2200	75	27	2P+2S+1N
5908	ST225/75R15 117/112L	E	BW	---	10	8.78	28.31	2830/2470	90	27	2P+2S+1N
5910	ST235/85R16 125/121L	E	BW	---	10	9.25	31.73	3640/3200	90	34	2P+2S+1N
5911	ST235/85R16 128/124L	F	BW	---	10	9.25	31.73	3960/3520	105	38	3P+2S+2N
5909	ST235/80R16 123/119L	E	BW	---	10	9.25	30.79	3420/3000	90	33	2P+2S+1N

DURATURN PASSENGER AND LIGHT TRUCK TIRE LIMITED WARRANTY

Duratur tires are made from the highest quality materials to very exacting manufacturing standards. Therefore, we back our tires with one of the industry's most comprehensive warranties. Duratur warrants that every new Duratur tire is free from defects in workmanship or material for five (5) years from the date of purchase (based on purchase receipt or invoice), six (6) years from the date of manufacture (based on the DOT code), or through the life of the original tread of a new tire less 2/32" of tread depth, whichever occurs first. The life of the original usable tread ends when the tire tread has worn down with only 2/32" remaining, at which point the tire is considered to be fully worn out.

This Limited Manufacturer's Warranty* applies to Duratur brand consumer tires purchased and operated in the United States, Canada or Puerto Rico which bear the complete description and serial number as required by the Department of Transportation (DOT).

1. What is covered by the Warranty and how long

Duratur's Limited Manufacturer's Warranty includes the following two warranties: Material and Workmanship Warranty and Limited Mileage Warranty. No other warranties are provided and/or included, subject to the provisions in section 5. All warranties contained herein are subject to the terms and conditions set forth herein.

a. Material and Workmanship Warranty:

If a defect in workmanship or material is found in any Duratur tire, Duratur will do either of the following:

- If an examination shows that a tire failed as a result of such defect during the first 2/32" of the original tread, Duratur will replace the tire with a comparable new Duratur tire free of charge. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.
- If an examination shows that a tire failed as a result of such defect after the first 2/32" of the original usable tread has worn out, a credit will be issued based on the percentage of usable tread depth remaining on the tire. Such credit will be deducted from a comparable new Duratur tire. The owner will be responsible for any remaining balance due after such credit is applied. All applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.
- Non-uniformity, including out-of-round, or out-of-balance adjustments, will only be accepted during the first 1/32" of tread wear. A claim for non-uniformity for a set of four (4) tires from the same vehicle will not be accepted.

b. Limited Mileage Warranty:

Many factors play a role in how fast any tire may wear out, including road conditions, driving habits, and proper vehicle and tire maintenance. Since every situation can be different, no manufacturer or dealer can guarantee you a certain number of miles from a tire. However, the following Duratur tires are warranted against tread wearing out prior to the indicated mileage (if the tire wears out evenly across the face of the tread before delivering the warranted mileage):

Light Truck Tires (Miles/km):

Duratur Travia H/T - 60,000/100,000
Duratur Travia A/T - 50,000/80,000

Passenger Car Tires (Miles/km):

Duratur Mozzo Touring - 70,000/110,000
Duratur Mozzo 4s - 45,000/75,000
Duratur Mozzo 4s+ - 50,000/80,000
Duratur Mozzo Sport - 50,000/80,000
Duratur Mozzo STX - 50,000/80,000

The Limited Mileage Warranty is applicable only for normal highway use when all of the Owner's Obligations listed in Section 4 are met. The Limited Mileage Warranty does not apply to any Duratur product(s) not listed above.

Prorated adjustment credit will be given based on the percentage of mileage not achieved by the tire. When applying the Limited Mileage Warranty, the consumer/owner will be responsible for the remaining price of (a) replacement tire(s), after the credit is deducted. This "remaining price" is calculated by multiplying the percentage of mileage not received, by the current retail sales price of the replacement Duratur tire(s). The consumer/owner is also responsible for any costs related to mounting, balancing and any other service charges or applicable taxes.

2. What is excluded from the Warranty

All Duratur warranties are limited to the original purchaser and the original vehicle on which the tire(s) are mounted.

Warranties are not assignable and/or transferable to subsequent owners, purchasers, or vehicles.

This Limited Warranty is applicable only in the United States, Canada or Puerto Rico; any tires used or equipped on a vehicle registered, owned, or operated outside the U.S., Canada or Puerto Rico are not covered by this warranty.

The following are not covered by this Limited Warranty:

- Tire marked "blem," "Non-Adjustable (N/A)," or previously adjusted.

Failure, damage, or irregular wear due to:

- Road hazards (i.e. punctures, cuts, snags, bruises, impact breaks, etc.), wreck or collision;
- Fire, accident, or vandalism;
- Mechanical condition of vehicle, including, but not limited to: misalignment, wheel imbalance, faulty shocks or brakes;
- Misapplication of tire or use of improper inner tube;
- Alteration of the tire, or addition of alien and/or foreign material;
- Use of tire chains;
- Off-roading, tire spinning, racing, or other competitive activities;
- Tires used in, or in connection with, commercial service(s); and
- Your vehicle having staggered tire fitments.
- Cost of mounting and/or balancing service(s).
- Costs related to tire pressure monitoring system(s).
- Loss of tire use, time, inconvenience, or any incidental or consequential damages.
- Improper use or operation including, but not limited to: improper tire and vehicle maintenance, run flat or run with severe under inflation, misuse, abuse, accident, fire or chemical corrosion, under inflation, overloading,

over deflection, or other failure to follow recommended rotation and maintenance practices.

- Improper installation, improper mounting or demounting, misapplication, improper repairs, wheel misalignment, or imbalance in the tire/wheel assembly.
- Any issues and/or failures resulting from use of a tire whose size, load and speed rating do not match the tire specifications outlined in the vehicle owner's manual and/or on the driver side door jamb placard.
- Tires with the Department of Transportation (DOT) number removed or rendered illegible; tires must bear the DOT prescribed tire identification numbers in order to qualify for any warranty made by Duratur.
- Ride complaints after the first 1/32" of tread wear or due to damaged wheels or any vehicle condition.

3. 30-Day Satisfaction Guarantee

Duratur offers a 30-Day Satisfaction Guarantee on our premium Mozzo Touring and Travia H/T tire lines. This guarantee is only available on the purchase of a set of four (4) tires. If you are not completely satisfied with your Mozzo Touring or Travia H/T tires, they can be returned to the original location of purchase within 30 days of purchase or the first 500 miles, whichever comes first. You must provide the original sales receipt and the reason you are not satisfied with the tires specified on the Duratur Tire Limited Warranty Claim form provided by your dealer. Your dealer will replace the tires or refund the purchase price including refunding mounting and balance. Not included are costs of any other service charges or applicable taxes.

Tires must be returned undamaged. Tires that have suffered damage due to road hazards or misuse or used in any competitive or racing activities are not eligible for this guarantee.

4. Owner's obligations

In order to be eligible for Duratur Limited Warranty service, owner must:

- Present the defective tire to an authorized Duratur dealer;
- Present proof of purchase to the satisfaction of the dealer;
- Complete, sign, and submit a Duratur Tire Limited Warranty Claim Form, available at any authorized dealer;
- In order to present a mileage warranty claim, submit proof of tire rotation according to the vehicle owner's manual recommendations or at least every 6,000 to 8,000 miles, along with the completed Tire Maintenance Record in this brochure.
- Pay the amount due on a new tire, including all applicable taxes, mounting and balancing charges and/or cost of other services ordered, less the amount of any applicable credit.
- Provide proof that at the time of purchase, the tire(s) were properly installed, balanced, and air pressure set to the vehicle manufacturer's specifications if original equipment size, or if at a different replacement size, then at an air pressure adequate to carry the vehicle load.
- Provide proof that, at least monthly, the owner or an authorized automotive service provider checked tire air pressure with a quality gauge and, if

necessary, adjusted to recommended cold PSI level as indicated in the vehicle owner's manual or the placard in the driver's side door jamb.

- Owner must have tires rebalanced if vibration is experienced, and alignment must be checked if unequal or rapid wear is occurring, or when scheduled by the vehicle maker.

Tires replaced on an adjustment basis become the property of YC Rubber Co. (North America) LLC, or its successors or assigns.

If you are unable to locate a Duratur tire dealer, you may contact Duratur Tire at 626-513-8989, or email to: info@duraturtires.com.

5. Your legal rights

This Limited Warranty gives you specific legal rights; you may also have other rights, which vary from state to state.

Duratur disclaims all other warranties, express or implied, including the implied warranty of merchantability, the implied warranty of fitness for a particular purpose and liability for incidental and consequential damages (i.e., loss of time, loss of use of vehicle, road services, towing charges, inconveniences, etc.)

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions may not apply to you.

No one (including a Duratur Tire employee, representative, or dealer) has the authority to vary the terms of this Limited Warranty.

Duratur Tire does not warrant any work performed by its dealers, their employees, or their representatives, including, but not limited to: selection, fitment, mounting and balancing, inspection, or repair of any tire.

Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer. Under no circumstances does this warranty constitute a representation that a tire failure cannot occur.

Once the tire is accepted by the Duratur dealer for adjustment under this Limited Warranty, you relinquish all ownership and rights to the tire.

6. Tire safety and maintenance information

Maintaining proper tire air pressure ensures safer, more comfortable driving and better fuel efficiency. Tire air pressure should be checked at least once per month because tires can lose 1 PSI (pounds per square inch) per month under normal conditions. Check your tires with a quality air gauge when the tires are "cold" - meaning the tires should not have been driven on for at least three hours. Follow your vehicle's owner's manual for proper inflation pressures and load carrying capacities. Never exceed tire maximum air pressure as listed on the tire's sidewall. Under-inflated, or over-inflated tires, will not perform as designed.

More information on tire safety and maintenance can be found in the Tire Care and Service Manual published by the Rubber Manufacturers Association (RMA) on their website: www.rma.org. Additional tire safety information can be found at www.safercar.gov.

* Duratur reserves the right to change the terms and conditions of all warranties at any time.



150 South Los Robles Avenue, Suite 400
Pasadena, CA 91101
(626) 513-8989
www.duraturntires.com

©2017 Duraturn Tires YC Rubber Co. (North America) LLC